



AG-TUF®

Indoor Corrugated PVC Liner Panel



AGRICULTURE



CONSTRUCTION



Overview

AG-TUF corrugated PVC liner panel allows efficient cladding with many benefits for the professional farmer.

Its chemical durability allows frequent cleaning for high sanitary maintenance and long service in harsh chemical environments.

AG-TUF panel is extremely easy to install and maintain using ordinary tools, while preserving its attractive glossy appearance over a long period of time.

Main Benefits

- Excellent sanitary capabilities
- Allows repeated cleaning cycles
- Excellent chemical resistance
- Resists livestock related gasses
- Rust-proof and easy to maintain
- Excellent light reflectance
- Mechanically durable
- Attractive high-gloss white finish
- Resists marking and scratching
- Non-flammable



Typical Applications

- Poultry Farms
- Pig Farms
- Dairies
- Barns
- Meat Packing
- Salt Storage
- Fertilizer Storage
- Loafing Sheds
- Fish Farms
- Factories
- Kennels
- Food Processing
- Car & Truck Washes
- Industrial Buildings
- Workshops
- Marinas







www.palram.com


Build On.

Product Range

Specification	Availability
Width (mm)	660 Up to 1,217
Length (m)	Up to 11.6
Thickness (mm)	0.8, 1.0, 1.2
Color	Bright White, Semi-Transparent White, Grey
Profile	Greca 76

Other Profiles*

Profile**	Iron 76	Greca 75	Greca 70
			
	3" Standard	American 2.6"	American 4.2"
			

* Available Upon Request, subject to a minimum quantity.

**Other profiles are available upon request.

Flammability

AG-TUF complies with the most demanding international fire resistance standards in the field of plastics, as indicated in the detailed table herein. The classification is subject to product type, thickness and color.

Standard	Classification*
ASTM D635-74	CC1

* For more detailed information please contact your Palram distributor.



Dairy milking parlour with AG-TUF cladded on the ceiling & walls.



Chicken Shed with AG-TUF cladded on the ceiling & walls.



PALRAM H.Q.

Tel: +972 4 8459.900
Fax: +972 4 8444.012
palram@palram.com

PALRAM EUROPE LTD.

Tel: +44 1302 380777
Fax: +44 1302 380788
sales.europe@palram.com

PALRAM AMERICAS

Tel: 610 285 9918
Fax: 610 285 9928
palramamericas@palram.com



61232 - 03.2019

In as much as Palram Industries has no control over the use to which others may put the material, it does not guarantee that the same results as those described herein will be obtained. Each user of the material should make his own tests to determine the material's suitability for his own particular use. Statements concerning possible or suggested uses of the materials described herein are not to be construed as constituting a license under any Palram Industries patent covering such use or as recommendations for use of such materials in the infringement of any patent. Palram Industries or its distributors cannot be held responsible for any losses incurred through incorrect installation of the material. In accordance with our company policy of continual product development you are advised to check with your local Palram Industries supplier to ensure that you have obtained the most up to date information.

©1997 Palram Industries Ltd. | AG-TUF is a registered trademark of Palram Industries Ltd.

